



SAFETY DATA SHEET

Revision Date 30-Apr-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name Gumout Expert Series Regane Fuel System Cleaner

Other means of identification

Product Code 31058
Document SKU 510060
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Fuel System Cleaner -
Uses advised against No information available

Details of the supplier of the safety data sheet

<u>Supplier Address</u>	<u>Manufacturer Address</u>	<u>Distributor</u>
ITW Global Brands 6925 Portwest Dr., Suite 100 Houston, TX 77024		

Company Phone Number 1-855-888-1988
24 Hour Emergency Phone Number (CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.)
(RMPDC) 1-877-504-9352 (U.S.)

E-mail address SDS@itwgb.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1B
Aspiration toxicity	Category 1

Label elements

Emergency Overview

Danger

May cause cancer
May be fatal if swallowed and enters airways
Combustible



Appearance Clear, yellow

Physical state Liquid

Odor Hydrocarbon

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash hands thoroughly after handling

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Keep out of reach of children

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin. Toxic to aquatic life with long lasting effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	30 - 60	*
DISTILLATES (PETROLEUM), SWEETENED MIDDLE	64741-86-2	10 - 30	*
POLYETHER AMINE	CONFIDENTIAL	10 - 30	*
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.	64742-94-5	1 - 5	*
NAPHTHALENE	91-20-3	<0.1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO₂, sand, earth, water spray or regular foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Combustible material. As this product contains combustible organic components, fire will produce dense smoke containing hazardous products of combustion.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and skin. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Slippery, can cause falls if walked on. Collect spillage. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep out of the reach of children.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
NAPHTHALENE 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles).
- Skin and body protection** Wear protective gloves and protective clothing.
- Respiratory protection** Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid
Appearance Clear, yellow
Odor Hydrocarbon
Odor threshold No information available

Property	Values	Remarks • Method
pH	Not Applicable	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	
Flash point	87.8°C / 190.0°F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	Not Determined	
Vapor density	No information available	

Relative density	0.85
Water solubility	Negligible
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	Not Determined
Density	0,85
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal use

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from all heat sources, open flames and other sources of ignition.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. May cause irritation of respiratory tract. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Ingestion may cause irritation to mucous membranes. May cause central nervous system depression. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
DISTILLATES (PETROLEUM), SWEETENED MIDDLE 64741-86-2	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 4.6 mg/L (Rat) 4 h

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
NAPHTHALENE 91-20-3	= 1110 mg/kg (Rat) = 490 mg/kg (Rat)	(= 1120 mg/kg (Rabbit) > 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
NAPHTHALENE 91-20-3	A3	Group 2A	Reasonably Anticipated	X

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5010 mg/kg
ATEmix (dermal) 2004 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	-	45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static	4720: 96 h Den-dronereides heteropoda mg/L LC50
DISTILLATES (PETROLEUM), SWEETENED MIDDLE 64741-86-2	-	35: 96 h Pimephales promelas mg/L LC50 flow-through	-
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. 64742-94-5	2.5: 72 h Skeletonema costatum mg/L EC50	19: 96 h Pimephales promelas mg/L LC50 static 41: 96 h Pimephales promelas mg/L LC50 2.34: 96 h Oncorhynchus mykiss mg/L LC50 1740: 96 h Lepomis macrochirus mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through	0.95: 48 h Daphnia magna mg/L EC50
NAPHTHALENE 91-20-3	0.4: 72 h Skeletonema costatum mg/L EC50	5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static 1.99: 96 h Pimephales promelas mg/L LC50 static 31.0265: 96 h Lepomis macrochirus mg/L LC50 static	2.16: 48 h Daphnia magna mg/L LC50 1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static 1.96: 48 h Daphnia magna mg/L EC50 Flow through

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

Disperses in water.

Chemical Name	Partition coefficient
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. 64742-94-5	2.9 - 6.1
NAPHTHALENE 91-20-3	3.3

Other adverse effects
No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Recover or recycle if possible. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U165

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
NAPHTHALENE 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145	-	U165

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
NAPHTHALENE 91-20-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
NAPHTHALENE 91-20-3	Toxic

14. TRANSPORT INFORMATION

DOT
Proper shipping name: Not regulated

IATA
Proper shipping name: Not regulated

IMDG

Proper shipping name: Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Not determined
IECSC	Not determined
KECL	Not determined
PICCS	Not determined
AICS	Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
NAPHTHALENE - 91-20-3	0.1

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NAPHTHALENE 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
NAPHTHALENE 91-20-3	1 lb	-	RQ 1 lb final RQ RQ 0.454 kg final RQ

US State Regulations

California Proposition 65

WARNING: This product contains a chemical(s) known to the State of California to cause cancer. This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
NAPHTHALENE - 91-20-3	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
NAPHTHALENE 91-20-3	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

<u>NFPA</u>	Health hazards 1	Flammability 2	Instability 0	-
<u>HMIS</u>	Health hazards 1	Flammability 2	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 30-Apr-2015
Revision Note 2

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet