



SAFETY DATA SHEET

Revision Date 29-May-2018

Version 2

1. IDENTIFICATION

Product identifier

Product Name Gumout Jet Spray Carb and Choke Cleaner

Other means of identification

Product Code 600951

Document SKU: 800002230, 800002231, 800002241

Recommended use of the chemical and restrictions on use

Recommended Use Carburetor Cleaner. Consumer Use.

Uses advised against All other applications

Details of the supplier of the safety data sheet

Supplier Address

ITW Global Brands
16200 Park Row, Suite 120
Houston, TX 77084

Manufacturer Address

Distributor

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

Company Phone Number

1-855-888-1988

24-hour emergency phone number

(CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.)

(RMPDC) 1-877-504-9352 (U.S.)

E-mail address

SDS@itwgb.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|----------------|
| Serious eye damage/eye irritation | Category 2 |
| Reproductive toxicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Flammable aerosols | Category 1 |
| Gases under pressure | Compressed gas |

Label elements

Emergency Overview

Signal word

Danger

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

**Appearance** Colorless**Physical state** Liquid Flammable Aerosol**Odor** Alcohol**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Wear eye/face protection
 Do not breathe dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Do not puncture or incinerate container
 Contents under pressure and can explode when exposed to heat or open flame
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Do not expose to temperatures exceeding 122 °F (50 °C)
 Keep away from heat, sparks, flames and other ignition sources
 Keep out of reach of children

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Causes mild skin irritation
- May be harmful if inhaled or swallowed
- Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

| Chemical Name | CAS No | Weight-% |
|----------------|----------|----------|
| ACETONE | 67-64-1 | 60 - 100 |
| TOLUENE | 108-88-3 | 5 - 10 |
| CARBON DIOXIDE | 124-38-9 | 5 - 10 |

Any concentration shown as a range is due to batch variation.

4. FIRST AID MEASURES

Description of first aid measures

| | |
|---|--|
| General advice | Get medical advice/attention if you feel unwell. |
| Eye contact | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Skin contact | IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse. |
| Inhalation | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician. |
| Ingestion | IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician. |
| Self-protection of the first aider | Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. |

Most important symptoms and effects, both acute and delayed

| | |
|-----------------|-------------------------------------|
| Symptoms | See section 2 for more information. |
|-----------------|-------------------------------------|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|------------------------|
| Note to physicians | Treat symptomatically. |
|---------------------------|------------------------|

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Dry chemical, CO₂, sand, earth, water spray or regular foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable. Contents under pressure and can explode when exposed to heat or flames. Vapors may cause flash fire.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

| | |
|-----------------------------|---|
| Personal precautions | Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and inhalation of vapors. Use personal protective equipment as required. Remove all sources of ignition. |
|-----------------------------|---|

Environmental precautions

| | |
|----------------------------------|---|
| Environmental precautions | See Section 12 for additional Ecological Information. |
|----------------------------------|---|

Methods and material for containment and cleaning up

| | |
|--|--|
| Methods for containment | Prevent further leakage or spillage if safe to do so. |
| Methods for cleaning up | Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. |
| Prevention of secondary hazards | Clean contaminated objects and areas thoroughly observing environmental regulations. |

7. HANDLING AND STORAGE

Precautions for safe handling

| | |
|--------------------------------|--|
| Advice on safe handling | Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. |
|--------------------------------|--|

Conditions for safe storage, including any incompatibilities

| | |
|-------------------------------|--|
| Storage Conditions | Keep containers tightly closed in a cool, well-ventilated place. Keep away from sunlight, ignition sources and other sources of heat. Do not expose to temperatures exceeding 50 °C/122 °F. Keep out of the reach of children. |
| Incompatible materials | Strong oxidizing agents |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------------------|----------------------------------|--|---|
| ACETONE 67-64-1 | STEL: 500 ppm TWA: 250 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³ |
| TOLUENE 108-88-3 | TWA: 20 ppm | TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ |
| CARBON DIOXIDE 124-38-9 | STEL: 30000 ppm TWA: 5000 ppm | TWA: 5000 ppm TWA: 9000 mg/m ³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m ³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m ³ | IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³ |

NIOSH IDLH *Immediately Dangerous to Life or Health*

| | |
|--------------------------|---|
| Other Information | Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). |
|--------------------------|---|

Appropriate engineering controls

| | |
|-----------------------------|--|
| Engineering Controls | Showers Eyewash stations Ventilation systems |
|-----------------------------|--|

Individual protection measures, such as personal protective equipment

| | |
|----------------------------|---|
| Eye/face protection | Wear safety glasses with side shields (or goggles). |
|----------------------------|---|

| | |
|---------------------------------------|--|
| Skin and body protection | Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves. |
| Respiratory protection | Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate. |
| General Hygiene Considerations | Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | |
|-----------------------|---------------------------|
| Physical state | Liquid; Flammable Aerosol |
| Appearance | Colorless |
| Odor | Alcohol |
| Odor threshold | No information available |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|--------------------------------|--------------------------|-------------------------|
| pH | No information available | |
| Melting point / freezing point | No information available | |
| Boiling point / boiling range | 56 °C / 133 °F | |
| Flash point | -20 °C / -4 °F | Tag Closed Cup |
| Evaporation rate | No information available | |
| Flammability (solid, gas) | No information available | |
| Flammability Limit in Air | | |
| Upper flammability limit: | 2.6 | |
| Lower flammability limit: | 12.8 | |
| Vapor pressure | 185 | |
| Vapor density | No information available | |
| Relative density | 0.798 | |
| Water solubility | Miscible in water | |
| Solubility in other solvents | No information available | |
| Partition coefficient | No information available | |
| Autoignition temperature | 465 °C / 869 °F | |
| Decomposition temperature | No information available | |
| Kinematic viscosity | No information available | |
| Dynamic viscosity | No information available | |
| Explosive properties | No information available | |
| Oxidizing properties | No information available | |

Other Information

| | |
|-------------------------|--------------------------|
| Softening point | No information available |
| Molecular weight | No information available |
| VOC Content (%) | 9.8% |
| Density | 0.797 g/cm3 |
| Bulk density | No information available |

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal use

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from all heat sources, open flames and other sources of ignition.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

| | |
|---------------------|---|
| Inhalation | May cause irritation of respiratory tract. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Harmful by inhalation. |
| Eye contact | Contact with eyes may cause irritation. May cause redness and tearing of the eyes. |
| Skin contact | May cause skin irritation and/or dermatitis. |
| Ingestion | Ingestion may cause irritation to mucous membranes. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed. |

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------------|----------------------|--------------------------|---------------------------------------|
| ACETONE 67-64-1 | = 5800 mg/kg (Rat) | - | = 50100 mg/m ³ (Rat) 8 h |
| TOLUENE 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---------------------|-------|---------|-----|------|
| TOLUENE 108-88-3 | - | Group 3 | - | - |

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Chronic toxicity May cause adverse liver effects.
Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, kidney, Liver, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5526 mg/kg
 ATEmix (dermal) 122449 mg/kg
 ATEmix (inhalation-dust/mist) 62 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity****Persistence and degradability**

No information available.

Bioaccumulation

No information available.

Mobility

Disperses in water.

| Chemical Name | Partition coefficient |
|---------------------|-----------------------|
| ACETONE 67-64-1 | -0.24 |
| TOLUENE 108-88-3 | 2.7 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods**

Disposal of wastes Recover or recycle if possible. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U002 U220

| Chemical Name | RCRA - Halogenated Organic Compounds | RCRA - P Series Wastes | RCRA - F Series Wastes | RCRA - K Series Wastes |
|---------------------|--------------------------------------|------------------------|---|------------------------|
| TOLUENE 108-88-3 | - | - | Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution. | - |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|---------------------|-----------------------------------|
| ACETONE 67-64-1 | Ignitable |
| TOLUENE 108-88-3 | Toxic Ignitable |

14. TRANSPORT INFORMATION**DOT**

UN/ID no UN 1950
Proper shipping name: Aerosols, flammable, Limited Quantity (LQ)
Hazard Class 2.1

IATA

UN/ID no UN 1950
Proper shipping name: Aerosols, flammable, Limited Quantity (LQ)
Hazard Class 2.1

IMDG

UN/ID no UN 1950
 Proper shipping name: Aerosols, flammable, Limited Quantity (LQ)
 Hazard Class 2.1

15. REGULATORY INFORMATION**International Inventories**

TSCA Complies
 DSL/NDL Complies
 EINECS/ELINCS Complies
 ENCS Not determined
 IECSC Not determined
 KECL Not determined
 PICCS Not determined
 AICS Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % |
|--------------------|-------------------------------|
| TOLUENE - 108-88-3 | 1.0 |

SARA 311/312 Hazard Categories

Acute health hazard No
 Chronic Health Hazard No
 Fire hazard No
 Sudden release of pressure hazard No
 Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| TOLUENE 108-88-3 | 1000 lb | X | X | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---------------------|--------------------------|----------------|--|
| ACETONE 67-64-1 | 5000 lb | - | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| TOLUENE 108-88-3 | 1000 lb 1 lb | - | RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 |
|--------------------|---------------------------|
| TOLUENE - 108-88-3 | Developmental |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|----------------------------|------------|---------------|--------------|
| ACETONE 67-64-1 | X | X | X |
| TOLUENE 108-88-3 | X | X | X |
| CARBON DIOXIDE 124-38-9 | X | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

| | | | | |
|-------------|------------------|----------------|--------------------|-----------------------|
| NFPA | Health hazards 2 | Flammability 3 | Instability 0 | - |
| HMIS | Health hazards 2 | Flammability 3 | Physical hazards 1 | Personal protection B |

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Revision Date 29-May-2018

Revision Note

4

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet