SAFETY DATA SHEET

1. Identification

Product identifier Gumout Silicone Lubricant

Other means of identification

Synonyms 29220

Recommended use Lubricant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name
Address
ITW Permatex Canada
c/o ITW Global Brands Canada
2360 Bristol Circle, Suite 101

Oakville, ON L6H 6M5

Telephone (905) 693-8900

E-mail CanadaCS@itwgb.com
Emergency phone number 800-255-3924 (Chem-Tel)

Supplier See above.

2. Hazard identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Liquefied gas
Simple asphyxiants Category 1
Aspiration hazard Category 1

Environmental hazards Not classified.

Label elements

Health hazards



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May displace

oxygen and cause rapid suffocation. May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Keep container tightly closed. Do not

pierce or burn, even after use.

Response IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Storage Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding

50°C/122°F. Store locked up.

Disposal Dispose of container in accordance with local, regional, national and international regulations.

Other hazards Combustible.

Supplemental information Exempt - Consumer product

This product is not subject to the Hazardous Products Act (HPA) Part II (Hazardous Products) as per paragraph 12(j); Schedule 1 (Non-Application of Part II). This restriction states that Part II does not apply in respect of the sale or importation of anything listed in Schedule 1 which includes any cosmetic, device, drug or food, as defined in section 2 of the Food and Drugs Act, or any consumer product as defined in section 2 of the Canada Consumer Product Safety Act.

Consult the product label for special protection or precautions that have been identified for using

this product under directed use conditions.

3. Composition/information on ingredients

Mixtures

#36013 Page: 1 of 7 Issue date 18-April-2023

Chemical name Common name and synonyms CAS number Distillates (petroleum), light 64742-47-8 10-30 hydrotreated All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. **Composition comments** CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret. 4. First-aid measures Inhalation If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention. Skin contact Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists. Eye contact Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Ingestion Most important Aspiration may cause pulmonary oedema and pneumonitis. Nausea, vomiting. Headache. symptoms/effects, acute and Dizziness. delayed Indication of immediate Provide general supportive measures and treat symptomatically. medical attention and special treatment needed General information If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children. 5. Fire-fighting measures Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Suitable extinguishing media Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media Contents under pressure. Pressurised container may explode when exposed to heat or flame. Specific hazards arising from During fire, gases hazardous to health may be formed. the chemical Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire. and precautions for firefighters Fire fighting In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. equipment/instructions Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards Extremely flammable aerosol. Contents under pressure. Pressurised container may explode when exposed to heat or flame. Combustible. Flammable properties Not available 6. Accidental release measures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Many gases Personal precautions, are heavier than air and will spread along ground and collect in low or confined areas (sewers, protective equipment and basements, tanks). Do not touch damaged containers or spilled material unless wearing emergency procedures appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section Methods and materials for Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate containment and cleaning up area). Keep combustibles (wood, paper, oil etc) away from spilled material. Large Spills: Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Do not discharge into lakes, streams, ponds or public waters. **Environmental precautions** 7. Handling and storage Pressurised container: Do not pierce or burn, even after use. Keep away from flames, such as a Precautions for safe handling pilot light, and any object that sparks, such as an electric motor. All equipment used when handling the product must be grounded. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash thoroughly after handling. When using do not eat or drink. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Conditions for safe storage, Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the including any incompatibilities

SDS). Keep out of reach of children. Store locked up.

8. Exposure controls/Personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Form Components Value Type Distillates (petroleum), light **TWA** 200 mg/m3 Vapour. hydrotreated (CAS

64742-47-8)

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and

Safety Regulation 296/97, as amended)

Form Components Value Type Distillates (petroleum), light **TWA** 200 mg/m3 Non-aerosol. hydrotreated (CAS 64742-47-8)

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 2020. S-15.1 Reg. 10. Table 18) **Form** Components **Type** Value

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

No biological exposure limits noted for the ingredient(s).

Biological limit values Exposure guidelines

Canada - Alberta OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS Can be absorbed through the skin.

15 minute

64742-47-8)

Canada - British Columbia OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS Can be absorbed through the skin.

64742-47-8)

Canada - Saskatchewan OELs: Skin designation

Can be absorbed through the skin. Distillates (petroleum), light hydrotreated (CAS

64742-47-8)

Appropriate engineering controls

exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment Wear safety glasses with side shields (or goggles).

Skin protection

Eye/face protection

Impervious gloves. Confirm with reputable supplier first. Hand protection

Other As required by employer code.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134),

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,

or other engineering controls to maintain airborne levels below recommended exposure limits. If

250 mg/m3

Vapour.

CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not smoke. When using do not eat or drink.

9. Physical and chemical properties

Aerosol **Appearance** Physical state Liquid. Form Liquefied gas. Not available. Colour Odour Mild

Odour threshold Not available. Not available. pН Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 38 °C (> 100.4 °F)

-104.0 °C (-155.2 °F) Flash point

#36013 Page: 3 of 7 Issue date 18-April-2023

Not available. **Evaporation rate** Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

(%)

Flammability limit - upper

Flammability limit - lower

Not available.

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper

Not available.

(%)

276 kPa Vapour pressure Not available. Vapour density

Relative density 0.94

Solubility(ies)

Not available. Solubility (water) Not available. **Partition coefficient** (n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available.

Other information

Viscosity

Explosive properties Not explosive. Oxidising properties Not oxidising VOC 20.5 %

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not mix

> with other chemicals. Strong oxidising agents.

Incompatible materials

Hazardous decomposition

products

May include and are not limited to: Oxides of carbon.

11. Toxicological information

Information on likely routes of exposure

Inhalation This product is an asphyxiant gas which can cause unconsciousness/death if OXYGEN levels are

sufficiently reduced. Signs and symptoms of preceding asphyxiation include and are not limited to rapid respiration, loss of mental alertness and co-ordination, dizziness, nausea and vomiting

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia. May cause stomach distress, nausea or vomiting.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary oedema and pneumonitis. Headache. Dizziness. Fatigue.

Nausea, vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. See below.

Components **Species Test Results**

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Acute Dermai

LD50 Rabbit > 2000 mg/kg, 24 Hours, ECHA

Inhalation

LC50 Rat > 5.3 mg/L, 4 Hours, ECHA Components Species Test Results

Oral

LD50 Rat > 5000 mg/kg, ECHA

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Exposure minutes Not available.

Erythema value Not available.

Oedema value Not available.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Corneal opacity valueNot available.Iris lesion valueNot available.Conjunctival reddeningNot available.

value

Conjunctival oedema value Not available.

Recover days Not available.

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitizer.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classified.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

Further information Not available.

12. Ecological information

Ecotoxicity See below

Ecotoxicological data

Components Species Test Results

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/L, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Mobility in soil No data available.

Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsContents under pressure. Do not puncture, incinerate or crush. Collect and reclaim or dispose in

sealed containers at licensed waste disposal site. Dispose of container in accordance with local,

regional, national and international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

Canada: TDG Proof of Classification: Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical

name and the classification of the product will appear below.

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN1950 **UN number**

AEROSOLS, flammable Proper shipping name

Hazard class 2.1

TDG

General



15. Regulatory information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Exempt - consumer product

This product is not subject to the Hazardous Products Act (HPA) Part II (Hazardous Products) as per paragraph 12(j); Schedule 1 (Non-Application of Part II). This restriction states that Part II does not apply in respect of the sale or importation of anything listed in Schedule 1 which includes any cosmetic, device, drug or food, as defined in section 2 of the Food and Drugs Act, or any consumer product as defined in section 2 of the Canada Consumer Product Safety Act.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

1 TONNES

Distillates (petroleum), light hydrotreated (CAS

64742-47-8)

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS status Hazardous

International regulations

Inventory status

Country(s) or region Inventory name On inventory (yes/no)* Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information



3 **FLAMMABILITY** PHYSICAL HAZARD 0 **PERSONAL PROTECTION**

3 2 0

Issue date 18-April-2023 **Effective date** 18-April-2023

Version No.

Other information For an updated SDS, please contact the supplier/manufacturer listed on the first page of the

document.

HEALTH

Disclaimer

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021