



SAFETY DATA SHEET

Revision Date 03-Oct-2019

Version 1

1. IDENTIFICATION

Product identifier

Product Name Gumout All In One Motorcycle Additive

Other means of identification

Product Code 10715
Document sku: 510159

Recommended use of the chemical and restrictions on use

Recommended Use Fuel System Cleaner -
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address
ITW Global Brands
16200 Park Row, Suite 120
Houston, TX 77084

Manufacturer Address
ITW ProfessionalAutomotive Products,
3606 Craftsman Blvd.Lakeland, Florida
33803

Manufactured and Distributed by:

May Also Be Distributed by:
ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

Distributor

Company Phone Number 1-855-888-1988
24-hour emergency phone number
(CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.)
(RMPDC) 1-877-504-9352 (U.S.)

E-mail address: SDS@itwgb.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 4

Label elements

Emergency Overview

Signal word

Danger

May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child
Causes damage to organs through prolonged or repeated exposure
Combustible liquid

Skin contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation persists, call a physician. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediate medical attention is not required. If symptoms persist, call a physician. Move to fresh air in case of accidental inhalation of vapors or decomposition products.
Ingestion	Do NOT induce vomiting. Aspiration of material due to vomiting can cause chemical pneumonitis which can be fatal. If vomiting occurs naturally, the victim should lean forward to reduce the risk of aspiration. Rinse mouth. Call a physician or poison control center immediately. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use, Dry chemical, Carbon dioxide (CO₂), Water spray (fog), Alcohol resistant foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges.

Environmental precautions

Environmental precautions See section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Soak up with inert absorbent material. Dam up. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
NAPHTHALENE 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
Benzene 71-43-2	STEL: 2.5 ppm TWA: 0.5 ppm S*	TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Clear liquid
Odor	Mild petroleum odor
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	> 49 °C / > 120 °F	
Flash point	> 78 °C / > 172 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	No information available	
Water solubility	No information available	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	3
Density	0.848 @22°C, 72°F
Bulk density	No information available
SADT (self-accelerating decomposition temperature)	No information available

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Not classifiable as a human carcinogen
 NTP (National Toxicology Program)
 Known - Known Carcinogen
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Benzene has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1).

Target Organ Effects Blood, bone marrow, Central nervous system, Eyes, kidney, Liver, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5212 mg/kg
ATEmix (dermal) 2020 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

11.875 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
Toluene 108-88-3	2.7
NAPHTHALENE 91-20-3	3.6
Benzene 71-43-2	2.1

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number U019 U165 U220 D018

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain	-

			chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
NAPHTHALENE 91-20-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-
Benzene 71-43-2	-	-	no data delivered	no data delivered

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Toluene 108-88-3	Toxic Ignitable
NAPHTHALENE 91-20-3	Toxic
Benzene 71-43-2	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT
Proper shipping name: Not regulated

IATA
Proper shipping name: Not regulated

IMDG
Proper shipping name: Not regulated

15. REGULATORY INFORMATION

International Inventories

- TSCA Complies
- DSL/NDSL Complies
- EINECS/ELINCS Complies
- ENCS Does not comply
- IECSC Complies
- KECL Complies
- PICCS Complies
- AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Toluene - 108-88-3	1.0
Benzene - 71-43-2	0.1
NAPHTHALENE - 91-20-3	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X
NAPHTHALENE 91-20-3	100 lb	X	X	X
Benzene 71-43-2	10 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
NAPHTHALENE 91-20-3	100 lb 1 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Benzene 71-43-2	10 lb	-	RQ 10 lb final RQ RQ 4.54 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Toluene 108-88-3	Developmental
Benzene 71-43-2	Carcinogen Developmental Male Reproductive
NAPHTHALENE	Carcinogen

