

# SAFETY DATA SHEET

Revision Date 23-Mar-2021 Version 4

# 1. IDENTIFICATION

Product identifier

Product Name Gumout Small Engine Jet Spray

Other means of identification

Product Code 450010

Document SKU:800002241

Recommended use of the chemical and restrictions on use

Recommended Use Carburetor Cleaner Consumer Use

Uses advised against All other applications

Details of the supplier of the safety data sheet

Supplier Address Manufacturer Address

Manufacturer Address

Distributor

ITW Global Brands 16200 Park Row, Suite 120 Houston, TX 77084

May Also Be Distributed by: ITW Permatex Canada 101-2360 Bristol Circle Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

**Company Phone Number** 

1-855-888-1988

24-hour emergency phone number

(CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.)

(RMPDC) 1-877-504-9352 (U.S.)

E-mail address: SDS@itwgb.com

# 2. HAZARDS IDENTIFICATION

# Classification

## **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

#### Label elements

# **Emergency Overview**

## Signal word Danger

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Colorless

Physical state Liquid Flammable Aerosol

Odor Alcohol

Revision Date 23-Mar-2021

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Do not puncture or incinerate container

Contents under pressure and can explode when exposed to heat or open flame

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

# **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

# **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Do not expose to temperatures exceeding 120 °F (49 °C)

Keep away from heat, sparks, flames and other ignition sources

Keep out of reach of children

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

Causes mild skin irritation. May be harmful if inhaled or swallowed. Harmful to aquatic life with long lasting effects.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
ACETONE	67-64-1	60 - 100
TOLUENE	108-88-3	5 - 10
CARBON DIOXIDE	124-38-9	5 - 10

4. FIRST AID MEASURES	
T. I INOT AID MEADONED	

3 .....

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

Revision Date 23-Mar-2021

advice/attention.

**Skin contact** IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician.

Take off contaminated clothing and wash before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, sand, earth, water spray or regular foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Extremely flammable. Contents under pressure and can explode when exposed to heat or flames. Vapors may cause flash fire.

**Explosion data** 

Sensitivity to Mechanical Impact Non

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and

inhalation of vapors. Use personal protective equipment as required. Remove all sources of

ignition.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

450010 - Gumout Small Engine Jet Spray

Revision Date 23-Mar-2021

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal. Use personal protective equipment as required.

Clean contaminated objects and areas thoroughly observing environmental regulations. Prevention of secondary hazards

### 7. HANDLING AND STORAGE

# Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing Advice on safe handling

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

#### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a cool, well-ventilated place. Keep away from sunlight,

ignition sources and other sources of heat. Do not expose to temperatures exceeding 50

°C/122 °F. Keep out of the reach of children.

Incompatible materials Strong oxidizing agents

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	
		(vacated) STEL: 2400 mg/m <sup>3</sup>	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
		industry. It is in effect for all other	
		sectors.	
		(vacated) STEL: 1000 ppm	
TOLUENE	TWA: 20 ppm	TWA: 200 ppm	IDLH: 500 ppm
108-88-3		(vacated) TWA: 100 ppm	TWA: 100 ppm
		(vacated) TWA: 375 mg/m <sup>3</sup>	TWA: 375 mg/m <sup>3</sup>
		(vacated) STEL: 150 ppm	STEL: 150 ppm
		(vacated) STEL: 560 mg/m <sup>3</sup>	STEL: 560 mg/m <sup>3</sup>
		Ceiling: 300 ppm	
CARBON DIOXIDE	STEL: 30000 ppm	TWA: 5000 ppm	IDLH: 40000 ppm
124-38-9	TWA: 5000 ppm	TWA: 9000 mg/m <sup>3</sup>	TWA: 5000 ppm
		(vacated) TWA: 10000 ppm	TWA: 9000 mg/m <sup>3</sup>
		(vacated) TWA: 18000 mg/m <sup>3</sup>	STEL: 30000 ppm
		(vacated) STEL: 30000 ppm	STEL: 54000 mg/m <sup>3</sup>
		(vacated) STEL: 54000 mg/m <sup>3</sup>	

NIOSH IDLH Immediately Dangerous to Life or Health

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 Other Information

(11th Cir., 1992).

Appropriate engineering controls

**Engineering Controls** Showers

> Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves. Skin and body protection

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of **General Hygiene Considerations** 

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Tag Closed Cup

9.1. Information on basic physical and chemical properties

Physical state Liquid Flammable Aerosol

**Appearance** Colorless Odor Alcohol

**Odor threshold** No information available

**Property** Values Remarks • Method

No information available Melting point / freezing point No information available

56 °C / 133 °F Boiling point / boiling range -20 °C / -4 °F Flash point

**Evaporation rate** No information available Flammability (solid, gas) No information available

Flammability Limit in Air

**Upper flammability limit:** 2.6 Lower flammability limit: 12.8 Vapor pressure 185

Vapor density No information available

Relative density 0.798

Water solubility Miscible in water

Solubility(ies) No information available **Partition coefficient** No information available

**Autoignition temperature** 465 °C / 869 °F

**Decomposition temperature** No information available Kinematic viscosity No information available **Dvnamic viscosity** No information available **Explosive properties** No information available Oxidizing properties No information available

**Other Information** 

Softening point No information available Molecular weight No information available

0.797 g/cm3 **Density** 

**Bulk density** No information available SADT (self-accelerating No information available

decomposition temperature)

# 10. STABILITY AND REACTIVITY

Reactivity

Stable under normal use

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from all heat sources, open flames and other sources of ignition.

#### Incompatible materials

Strong oxidizing agents

#### **Hazardous Decomposition Products**

Carbon oxides

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract. May cause central nervous system depression with

nausea, headache, dizziness, vomiting, and incoordination. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Harmful by

Revision Date 23-Mar-2021

inhalation.

**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis.

**Ingestion** Ingestion may cause irritation to mucous membranes. Potential for aspiration if swallowed.

Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg ( Rabbit )	= 50100 mg/m³ (Rat) 8 h
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L (Rat) 4 h

#### Information on toxicological effects

**Symptoms** No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE	-	Group 3	-	-
108-88-3		,		

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

**Chronic toxicity** May cause adverse liver effects.

Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, kidney, Liver, Respiratory

system, Skin.

# The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5526 mg/kg
ATEmix (dermal) 122449 mg/kg
ATEmix (inhalation-dust/mist) 62 mg/l

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

#### Mobility

Disperses in water.

Chemical Name	Partition coefficient
ACETONE	-0.24
67-64-1	
TOLUENE	2.7
108-88-3	

### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recover or recycle if possible. Disposal should be in accordance with applicable regional, Disposal of wastes

national and local laws and regulations.

Do not reuse container. Contaminated packaging

**US EPA Waste Number** D001

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE	-	-	Toxic waste	=
108-88-3			waste number F025	
			Waste description:	
			Condensed light ends, spent	
			filters and filter aids, and	
			spent desiccant wastes from	
			the production of certain	
			chlorinated aliphatic	
			hydrocarbons, by free	
			radical catalyzed processes.	
			These chlorinated aliphatic	
			hydrocarbons are those	
			having carbon chain lengths	
			ranging from one to and	
			including five, with varying	
			amounts and positions of	
			chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE	Ignitable
67-64-1	, and the second
TOLUENE	Toxic
108-88-3	Ignitable

# 14. TRANSPORT INFORMATION

<u>DOT</u>

**UN/ID No** UN 1950

Aerosols, Flammable Liquid NOS (Petroleum Distillates), Limited Quantity (LQ) Proper shipping name

**Hazard Class** 2.1

IATA

**UN/ID No** UN 1950

Proper shipping name Aerosols, Flammable Liquid NOS (Petroleum Distillates), Limited Quantity (LQ)

Hazard Class 2.1

<u>IMDG</u>

**UN/ID No** UN 1950

Proper shipping name Aerosols, Flammable Liquid NOS (Petroleum Distillates), Limited Quantity (LQ)

Hazard Class 2.

# 15. REGULATORY INFORMATION

#### **International Inventories**

**TSCA** Complies **DSL/NDSL** Complies Complies **EINECS/ELINCS** Does not comply **ENCS** Complies **IECSC** Does not comply **KECL PICCS** Complies **AICS** Does not comply

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
TOLUENE - 108-88-3	1.0	
SARA 311/312 Hazard Categories		
Acute health hazard	No	
Chronic Health Hazard	No	
Fire hazard	No	
Sudden release of pressure hazard	No	
Reactive Hazard	No	

### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	Х	X	Х

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE	5000 lb	<del>-</del>	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
TOLUENE	1000 lb 1 lb	<del>-</del>	RQ 1000 lb final RQ
108-88-3			RQ 454 kg final RQ RQ 1 lb final
			RQ

	RQ 0.454 kg final RQ

# **US State Regulations**

**California Proposition 65** 

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
TOLUENE	Developmental
108-88-3	'

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE	X	X	X
67-64-1			
TOLUENE	X	X	X
108-88-3			
CARBON DIOXIDE	X	X	X
124-38-9			

### **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

### **WHMIS Hazard Class**

Non-controlled

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Instability 0 Health hazards 2 Flammability 3 NFPA

HMIS Health hazards 2 Flammability 3 Physical hazards 1 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

23-Mar-2021 **Revision Date** 

**Revision Note** 4

### Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**