

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Gumout® 120DA Belt Dressing

**Other means of identification**

**Synonyms** 80552

**Recommended use** Lubricant

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name** ITW Permatex Canada  
**Address** c/o ITW Global Brands Canada  
2360 Bristol Circle, Suite 101  
Oakville, ON L6H 6M5  
**Telephone** (905) 693-8900  
**E-mail** literature.canada@permatex.com

**Emergency phone number** 800-255-3924 (Chem-Tel)

**Supplier** See above.

## 2. Hazard identification

<b>Physical hazards</b>	Flammable aerosols	Category 2
	Gases under pressure	Liquefied gas
	Simple asphyxiants	Category 1
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity following repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Not classified.	

**Label elements**



**Signal word** Danger

**Hazard statement** Flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes skin irritation.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.  
May be fatal if swallowed and enters airways.  
May displace oxygen and cause rapid suffocation.

**Precautionary statement**

**Prevention**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.  
Do not breathe mist or vapour.  
Wash thoroughly after handling.  
Wear protective gloves, protective clothing, eye protection and face protection.

**Response**

IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label).  
IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.  
IF exposed or concerned: Get medical attention.

<b>Storage</b>	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.
<b>Disposal</b>	Dispose of container in accordance with local, regional, national and international regulations.
<b>Other hazards</b>	None known.
<b>Supplemental information</b>	Exempt - Consumer product
<p>This product is not subject to the Hazardous Products Act (HPA) Part II (Hazardous Products) as per paragraph 12(j); Schedule 1 (Non-Application of Part II). This restriction states that Part II does not apply in respect of the sale or importation of anything listed in Schedule 1 which includes any cosmetic, device, drug or food, as defined in section 2 of the Food and Drugs Act, or any consumer product as defined in section 2 of the Canada Consumer Product Safety Act. Consult the product label for special protection or precautions that have been identified for using this product under directed use conditions.</p>	

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butene, homopolymer		9003-29-6	5 - 10 *
Hexane		110-54-3	7 - 13 *
Petroleum gases, liquefied, sweetened		68476-86-8	3 - 7 *

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** \*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
<b>Skin contact</b>	IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label).
<b>Eye contact</b>	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
<b>Ingestion</b>	IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up.
<b>Specific methods</b>	Move containers from fire area if you can do so without risk. Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Flammable aerosol. Contents under pressure. Pressurised container may explode when exposed to heat or flame.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breathe mist or vapour. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see Section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.
<b>Environmental precautions</b>	Do not discharge into lakes, streams, ponds or public waters.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces. - No smoking. Pressurised container: Do not pierce or burn, even after use. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Do not breathe mist or vapour. Use only in well-ventilated areas. Pregnant or breastfeeding women must not handle this product. Avoid prolonged exposure. Observe good industrial hygiene practices. Wash thoroughly after handling. When using do not eat or drink.
<b>Conditions for safe storage, including any incompatibilities</b>	Keep away from heat, sparks and open flame. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children. Store locked up.

## 8. Exposure controls/Personal protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Hexane (CAS 110-54-3)	TWA	50 ppm

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Hexane (CAS 110-54-3)	TWA	176 mg/m3 50 ppm

#### Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Hexane (CAS 110-54-3)	TWA	20 ppm

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Hexane (CAS 110-54-3)	TWA	50 ppm

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Hexane (CAS 110-54-3)	TWA	50 ppm

#### Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
Hexane (CAS 110-54-3)	TWA	176 mg/m3 50 ppm

#### Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Hexane (CAS 110-54-3)	15 minute	62.5 ppm

Components	Type	Value
	8 hour	50 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Hexane (CAS 110-54-3)	0.5 mg/L	2,5-Hexanedione, without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****Canada - Alberta OELs: Skin designation**

Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**Canada - Manitoba OELs: Skin designation**

Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**Canada - Ontario OELs: Skin designation**

Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**Canada - Quebec OELs: Skin designation**

Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**Appropriate engineering controls**

Ensure adequate ventilation.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear appropriate chemical resistant gloves. Confirm with a reputable supplier first.

**Other**

As required by employer code.

**Respiratory protection**

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

**Thermal hazards**

Not applicable.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.

**9. Physical and chemical properties**

<b>Appearance</b>	Aerosol
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquefied gas.
<b>Colour</b>	White
<b>Odour</b>	Solvent
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	> 38 °C (> 100.4 °F)
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	< 1
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.

<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit – upper (%)</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	> 1 (Air = 1)
<b>Relative density</b>	0.97
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Soluble
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.
<b>VOC</b>	15 %

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerisation does not occur.
<b>Conditions to avoid</b>	Heat. Do not mix with other chemicals.
<b>Incompatible materials</b>	Strong oxidising agents.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. May cause damage to organs through prolonged or repeated exposure by inhalation.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Aspiration may cause pulmonary oedema and pneumonitis. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.
-------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Information on toxicological effects

<b>Acute toxicity</b>	May be fatal if swallowed and enters airways.
-----------------------	-----------------------------------------------

Components	Species	Test Results
Butene, homopolymer (CAS 9003-29-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rat	> 2020 mg/kg, Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 6360 mg/m3, ECHA
<i>Oral</i>		
LD50	Rat	> 5050 mg/kg, ECHA
Hexane (CAS 110-54-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5 ml/kg, 4 Hours, ECHA

Components	Species	Test Results
		3350 mg/kg, ECHA
<i>Inhalation</i> LC50	Rat	259354 mg/m³, 4 Hours, ECHA 73860 ppm, 4 Hours, ECHA
<i>Oral</i> LD50	Rat	16000 mg/kg, ECHA
Petroleum gases, liquefied, sweetened (CAS 68476-86-8)		
<b>Acute</b>		
<i>Dermal</i> LD50	Not available	
<i>Inhalation</i> LC50	Rat	1442738 mg/m3, 10 Minutes, ECHA 1443 mg/L, 10 Minutes, ECHA
<i>Oral</i> LD50	Not available	
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitisation</b>		
<b>Respiratory sensitisation</b>	Not a respiratory sensitizer.	
<b>Skin sensitisation</b>	This product is not expected to cause skin sensitisation.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Contains < 3% (w/w) DMSO-extract	
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.	
<b>Specific target organ toxicity - single exposure</b>	Not classified.	
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	May cause damage to organs through prolonged or repeated exposure. Peripheral nerve damage has been observed following occupational exposure to n-hexane.	
<b>Further information</b>	Not available.	

## 12. Ecological information

Ecotoxicity	See below		
Ecotoxicological data			
Components	Species		Test Results
Hexane (CAS 110-54-3)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential			
Mobility in soil	No data available.		
Mobility in general	Not available.		

<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.
------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### 13. Disposal considerations

<b>Disposal instructions</b>	Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

### 14. Transport information

<b>General</b>	Canada: TDG Proof of Classification: Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
----------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### Transportation of Dangerous Goods (TDG - Canada)

##### Basic shipping requirements:

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	AEROSOLS, flammable
<b>Hazard class</b>	2.1
<b>Special provisions</b>	80, 107

TDG



### 15. Regulatory information

<b>Canadian federal regulations</b>	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.
-------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------

Exempt- consumer product

This product is not subject to the Hazardous Products Act (HPA) Part II (Hazardous Products) as per paragraph 12(j); Schedule 1 (Non-Application of Part II). This restriction states that Part II does not apply in respect of the sale or importation of anything listed in Schedule 1 which includes any cosmetic, device, drug or food, as defined in section 2 of the Food and Drugs Act, or any consumer product as defined in section 2 of the Canada Consumer Product Safety Act.

#### Canada CEPA Schedule I: Listed substance

Petroleum gases, liquefied, sweetened (CAS 68476-86-8)	Listed.
--------------------------------------------------------	---------

#### Canada DSL Challenge Substances: Listed substance

Hexane (CAS 110-54-3)	Listed
-----------------------	--------

#### Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Hexane (CAS 110-54-3)	1 TONNES
-----------------------	----------

#### Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### Greenhouse Gases

Not listed.

#### Precursor Control Regulations

Not regulated.

<b>WHMIS status</b>	Hazardous
---------------------	-----------

#### International regulations

<b>WHMIS classification</b>	Exempt - Consumer product
-----------------------------	---------------------------

**Inventory status****Country(s) or region**

Canada

Canada

**Inventory name**

Domestic Substances List (DSL)

Non-Domestic Substances List (NDSL)

**On inventory (yes/no)\***

Yes


No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**16. Other information**

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		1
PERSONAL PROTECTION		X

**Issue date**

12-June-2020

**Revision date**

12-June-2020

**Version No.**

03

**Other information**

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

**Disclaimer**

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Prepared by**

Dell Tech Laboratories Ltd. Phone: (519) 858-5021